



**ELECTRICAL CHARACTERISTICS:**  
CONTACT CURRENT RATING: 1 AMP.

DIELECTRIC WITHSTANDING VOL TAGE: AC 500V R.M.  
INSULATION RESISTANCE: 500 MEGOHMS MINIMUM AT  
DC 500V  
CONTACT RESISTANCE: 30 MILLIOHMS MAXIMUM

特性: Specifications:  
电学: Electrical:  
接触电阻: Contact Resistance  
30 milliohms MAX  
耐电压: Dielectric Withstanding Voltage:  
500 V AC 50 Sea level.  
绝缘电阻: Insulation Resistance:  
1000 MEGA ohms MIN

结构: Mechanical:  
配合力 Mating Force:  
4.0 磅 KAW 4.0 kg  
插力 Inserting Force:  
0.7 磅 MK 0.7 kg

材料: Material:  
壳体: Housing: High Temperature Thermoplastic.  
LW-0 耐高温塑胶  
端子: Contact: Copper Alloy 铜合金  
壳体: Shell: Copper Alloy 铜合金

电镀: Finish:  
端子: Contact: Plated Gold in Mating Area;  
Two Lead On Solder Lette  
接触点镀金, 引脚镀锌

壳体: Shell:  
Tin/Lead Plating 镀锡铅  
Nickel Plating 镀锌

<b>OWL ELECTRONICS LIMITED</b>					成稿图
品名	ST 3108PC	质	单位	罐	
图号	HT0808	图纸编号	比例	1:1	
制图	段向刚	审核	段向刚	日期	2004.02.23